

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010

Page 1 of 7

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : **GU-PLAST PVC REINIGER ANLÖSEND**

Product Code(s) : 9-38970-00-0-0

Product Use : Cleaning agent / Detergent

Chemical Family : Mixture.

Supplier's name and address:
Ferco Ferrures de bâtiment
2000, rue Berlier
Laval, QC, Canada
H7L 4S4

Information Telephone # : (514) 973-1437

24 Hr. Emergency Tel # : Not available.

Manufacturer's name and address:
Refer to Supplier

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). WHMIS classification:
Class B2 (Flammable Liquids).

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). Hazardous classification:
Flammable liquid; Acute Health Hazard; Chronic Health Hazard.

Emergency Overview : Clear, colourless liquid. Fruity odour. **WARNING!** Flammable liquid and vapour. Vapour is heavier than air and will collect in low-lying places. Vapour may cause flash fire! May be harmful if inhaled or swallowed. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. Prolonged or repeated skin contact may cause drying and irritation. Prolonged overexposure may cause liver and kidney effects.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Skin : Direct skin contact may result in little or no irritation.

Eyes : May cause mild eye irritation. Symptoms will include pain, redness and tearing.

Ingestion : May cause irritation of mouth, throat, and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Prolonged overexposure may cause liver and kidney effects.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS #	Wt.%
Ethyl acetate	141-78-6	60.00 - 100.00
n-Butyl acetate	123-86-4	0.10 - 0.50

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010

Page 2 of 7

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Remove exposed person to fresh air immediately. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stopped, begin artificial respiration. Get medical attention.
- Skin contact** : Flush contaminated area with lukewarm, gently running water for at least 5 to 10 minutes or until the chemical is removed. Remove contaminated clothing. If skin irritation or rash occurs, seek medical advice/attention. Wash contaminated clothing before reuse.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Ingestion** : Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Have victim rinse mouth with water, then give one to two glasses of water to drink. Obtain medical attention immediately.
- Notes For Physician** : Treat symptomatically. This product is a CNS depressant.

SECTION 5 - FIRE FIGHTING MEASURES

- Fire hazards/conditions of flammability** : Flammable liquid and vapour. Vapours may form explosive mixture with air. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapours are heavier than air and collect in confined and low-lying areas. Vapours may cause flash fire.
- Flammability classification (OSHA 29 CFR 1910.1200)** : Flammable Liquid Class 1B.
- Oxidizing properties** : None known.
- Explosion data: Sensitivity to mechanical impact / static discharge** : Not expected to be sensitive to mechanical impact. Product will accumulate static charge. Mixtures of vapour and air at concentrations in the flammable range may be ignited by a static discharge of sufficient energy.
- Suitable extinguishing media** : Dry chemical, foam, carbon dioxide and water fog.
- Special fire-fighting procedures/equipment** : During a fire, irritating and toxic gases may be generated by thermal decomposition or combustion. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.
- Hazardous combustion products** : Carbon oxides and other irritating fumes and smoke.
- NFPA Rating**

0 - Minimal	1 - Slight	2 - Moderate	3 - Serious
<i>Health: 1</i>	<i>Flammability: 3</i>	<i>Instability: 0</i>	<i>Special Hazards: None</i>

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
- Environmental precautions** : Do not allow material to contaminate ground water system. For large spills, dike the area to prevent spreading.
- Spill response/cleanup** : Ventilate area of release. Eliminate all ignition sources. Remove combustible materials. Stop the spill at source if it is safe to do so. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010

Page 4 of 7

Boiling point	: 76°C (168.8°F)	Specific gravity	: 0.9
Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av
Vapour pressure (mmHg @ 20° C / 68° F)	: 75	Solubility in water	: Moderate (79 g/L @ 20°C / 68°F)
Vapour density (Air = 1)	: > 1	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Volatile organic Compounds (VOC's)	: N/Av	Volatiles (% by weight)	: N/Av
Flash point	: - 4°C (24.8°F)	Auto-ignition temperature	: 460°C(860°F)
Flash point Method	: closed cup	Upper flammable limit (% by vol.)	: 11.5
Lower flammable limit (% by vol.)	: 2.1	Flashback observed	: N/Av
Flame Projection Length	: N/Av		

Section 10: Stability And Reactivity

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed. In the presence of water, product may slowly hydrolyze to ethyl alcohol and acetic acid.
Hazardous polymerization	: Hazardous polymerisation does not occur.
Conditions to avoid	: Avoid heat, open flames, sparks, static electricity and electrical equipment. Keep away from direct sunlight.
Materials To Avoid And Incompatibility	: See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products	: acetic acid; Ethanol. Refer to Section 5 for additional 'Hazardous combustion products'.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, digestive system, central nervous system.
Routes of exposure	: <i>Inhalation</i> : YES <i>Skin Absorption</i> : NO <i>Skin & Eyes</i> : YES <i>Ingestion</i> : YES
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀(4hr)</u> <u>inh. rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Ethyl acetate	19,600 ppm	5600 mg/kg	> 18,000 mg/kg
n-Butyl acetate	1802 mg/m ³ (aerosol); 2000 ppm (vapour)	7400 mg/kg	> 5000 mg/kg

Carcinogenic status	: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
Reproductive effects	: None known.
Teratogenicity	: None known.
Mutagenicity	: None known.
Epidemiology	: Not available.
Sensitization to material	: Not expected to be a skin or respiratory sensitizer.
Synergistic materials	: None known or reported by the manufacturer.
Irritancy	: Mild.
other important hazards	: CNS depression may result from extreme exposures.
Conditions aggravated by overexposure	: Pre-existing skin, eye and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	: No information available. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
Mobility	: No data is available on the product itself.

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010



Page 5 of 7

- Persistence** : No data is available on the product itself.
Bioaccumulation potential : No data is available on the product itself.
Other Adverse Environmental effects
: No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Store material for disposal as indicated in Handling and Storage (Section 7). Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (ethyl acetate; butyl acetates)	3	II	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, is shipping under this exemption.				
49CFR/DOT	UN1993	Flammable Liquids, n.o.s. (Contains: Ethyl acetate; Butyl acetate)	3	II	
49CFR/DOT Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Refer to 49 CFR Section 173.150.				

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): ethyl acetate (5000 lbs / 2270 kg).

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: ethyl acetate (CA, MA, MN, NJ, PA, RI);n-Butyl acetate (CA, MA, MN, NJ, PA, RI).

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010

Page 6 of 7

International Information:

WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA): Mixture. All components of this product are on the Canadian DSL list.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating	:	* - Chronic hazard	0 - Minimal	1 - Slight	2 - Moderate	3 - Serious
		<i>Health: *1</i>		<i>Flammability: 3</i>		<i>Reactivity: 1</i>

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CNS: Central Nervous System
- DOT: Department of Transportation
- DSL: Domestic Substances List
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- LC: Lethal Concentration
- LD: Lethal Dose
- MA: Massachusetts
- MN: Minnesota
- N/Ap: Not Applicable
- N/Av: Not Available
- NFPA: National Fire Protection Association
- NIOSH: National Institute of Occupational Safety and Health
- NJ: New Jersey
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PA: Pennsylvania
- PEL: Permissible exposure limit
- RCRA: Resource Conservation and Recovery Act
- RI: Rhode Island
- RTECS: Registry of Toxic Effects of Chemical Substances
- SARA: Superfund Amendments and Reauthorization Act
- STEL: Short Term Exposure Limit
- TDG: Canadian Transportation of Dangerous Goods Act & Regulations
- TLV: Threshold Limit Values
- TSCA: Toxic Substance Control Act
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009.
- 2. International Agency for Research on Cancer Monographs, searched 2010.
- 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2010 (Chempendium, HSDB, RTECS).
- 4. Material Safety Data Sheet from manufacturer.
- 5. US EPA Title III List of Lists - October 2006 version.
- 6. California Proposition 65 List - February 5, 2010 version.

GU-PLAST PVC REINIGER ANLÖSEND

MSDS Revision Date (dd/mm/yyyy): 01/03/2010

Page 7 of 7

<p>Prepared for: Ferco Ferrures de bâtiment 2000, Rue Berlier Laval, Qué (Canada), H7L 4S4 Please direct all inquiries to Ferco Ferrures de bâtiment.</p>	
<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	 <p>HAZARDOUS – MATERIALS REGULATIONS SPECIALISTS</p>

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from Ferco Ferrures de bâtiment and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Ferco Ferrures de bâtiment expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and Ferco Ferrures de bâtiment.

Preparation Date (dd/mm/yyyy)

: 13/11/2008

Reviewed Date (dd/mm/yyyy)

: 01/03/2010

Revision No.

: 2

Revision Information

: Sections 2 and 3, switched.
(M)SDS sections updated:
2. HAZARDS IDENTIFICATION;
3. COMPOSITION/INFORMATION ON INGREDIENTS;
5. FIRE-FIGHTING MEASURES;
9. PHYSICAL AND CHEMICAL PROPERTIES;
11. TOXICOLOGICAL INFORMATION;
12. ECOLOGICAL INFORMATION;
14. TRANSPORT INFORMATION;
15. REGULATORY INFORMATION.

END OF DOCUMENT